

NOTES



For further information,
contact the nearest RBA Group office:
SYDNEY • MELBOURNE • BRISBANE
Phone: 1300 788 778 • Fax: 1300 788 878
info@rba.com.au • www.rba.com.au



INSTALLATION INSTRUCTIONS

MODEL A8853-DIS-FM FROUNT MOUNT



COMPONENTS

"P" Trap Stainless Steel Pan
Security bit

"S" Trap converter
Mounting Frame

PRE-INSTALLATION

Installation should be in accordance with local authority and statutory requirements, and as per these installation instructions.

Pan is "wall faced" and should preferably be fixed to a masonry wall with suitable wall anchors provided by others. Supplied with "S" trap converter to allow either "S" or "P" configuration.

This model supplied pre drilled for toilet seat, ordered separately.

Flushing device should be –
Fowler Tasman Mk 2 cistern
Geberit Compact model no. 110.707.PN.1

INSTALLATION

- 1) If not pre-formed, make sufficient penetrations through the wall, as determined from the drawing, to allow the 100 mm waste pipe and 50 mm flush pipe, to pass through.
- 2) Fit the mounting frame to the wall in a location determined from the drawing, using suitable wall anchors supplied by others.
- 3) Fit a 100 mm pan collar to the outlet with sufficient 100 mm pipe to extend through the wall. (Alternately the waste and flush pipes may be pre-plumbed and the pan pushed onto the pipework.) If "S" trap configuration is required, location of floor penetration should be determined from the drawing.
- 4) Similarly fit a 50 mm keeseal to the pan inlet with sufficient pipe, as provided by the cistern manufacturer, to extend through the wall.
- 5) Push the pan into position and secure the pan to the wall.
- 6) Make the necessary connections to the waste, and install the cistern and connect according to the manufacturers instructions.

INSTALLATION

- 7) Check for leaks and correct flush volumes, 6 litres full flush and 3 litres half flush.
- 8) If fitting a seat, remove access panel, fit seat and replace.

- 1 55mm I.D. Flushing Inlet. Keeseal By Others.
- 2 100mm O.D. Waste Outlet.
- 3 Wall Anchors And Anchoring Hardware Are By Others.
- 4 Mounting Channel With 13mm Diameter x 22mm Long, Wall Mounting Slots.
- 5 Vandal Resistant Fasteners.
- 6 Access Panels On Both Sides Of Toilet Housing Are Secured With Vandal Resistant Fasteners.

