

## NOTES



For further information,  
contact the nearest RBA Group office:  
SYDNEY • MELBOURNE • BRISBANE  
Phone: 1300 788 778 • Fax: 1300 788 878  
info@rba.com.au • www.rba.com.au



## INSTALLATION INSTRUCTIONS

**MODEL A8853-FM FRONT MOUNT**



## COMPONENTS

"P" Trap Stainless Steel Pan  
Security bit

"S" Trap converter  
Mounting Frame

## PRE-INSTALLATION

Installation should be in accordance with local authority and statutory requirements, and as per these installation instructions.

Pan is "wall faced" and should preferably be fixed to a masonry wall with suitable wall anchors provided by others. Supplied with "S" trap converter to allow either "S" or "P" configuration.

Flushing device should be –  
Fowler Tasman Mk 2 cistern  
Geberit Compact model no. 110.707.PN.1

## INSTALLATION

- 1) If not pre-formed, make sufficient penetrations through the wall, as determined from the drawing, to allow the 100 mm waste pipe and 50 mm flush pipe, to pass through.
- 2) Fit the mounting frame to the wall in a location determined from the drawing, using suitable wall anchors supplied by others.
- 3) Fit a 100 mm pan collar to the outlet with sufficient 100 mm pipe to extend through the wall. (Alternately the waste and flush pipes may be pre-plumbed and the pan pushed onto the pipework.) If "S" trap configuration is required, location of floor penetration should be determined from the drawing.
- 4) Similarly fit a 50 mm keeseal to the pan inlet with sufficient pipe, as provided by the cistern manufacturer, to extend through the wall.
- 5) Push the pan into position and secure the pan to the wall.
- 6) Make the necessary connections to the waste, and install the cistern and connect according to the manufacturers instructions.
- 7) Check for leaks and correct flush volumes, 6 litres full flush and 3 litres half flush.
- 8) If fitting a seat, remove access panel, fit seat and replace.

## INSTALLATION

- 1 55mm I.D. Flushing Inlet. Keyseal By Others.
- 2 100mm O.D. Waste Outlet.
- 3 Wall Anchors And Anchoring Hardware Are By Others.
- 4 Mounting Channel With 13mm Diameter x 22mm Long, Wall Mounting Slots.
- 5 Vandal Resistant Fasteners.
- 6 Access Panels On Both Sides Of Toilet Housing Are Secured With Vandal Resistant Fasteners.

